

■ POWER SUPPLY

Wall mount type

(input:AC 100~240V,50/60Hz,output: DC 12V/1A) OR

Built-in type *For dental unit

(input : AC 20~30V,50/60Hz, output: DC 12V/1.25A)

■ Optional Accessories



φ 8mm,Transparent,45°



φ 8mm,Black,60°



φ 4mm,Black,60°

ULight™



GB-070

LED Curing Light

■ Mono LCD version

FINE VISION ELECTRONICS CO.,LTD.

11/F.,NO123-8,HSING TE RD.,
SANCHUNG CITY,TAIPEI COUNTY
TAIWAN R.O.C.

TEL:886-2-85123668

FAX:886-2-85123678

Web Site : www.finevision.com.tw

E-mail : info@finevision.com.tw

FVE

2009/2

CE GMP

FVE Professional in Dentistry
Dental curing light major manufacturer

High intensity output

The ULight™ is offered with a super high luminosity LED. The light wavelength is between 440nm and 480nm and the intensity is more than 1000mW/cm². It is an applicable tool. The ULight™ can work effectively within almost photosensitive polymerized composites.

Easy read LCD display

Easy to operate by GUI (graphic user interface)



The GB-070 is used by mono LCD display with icon. It is easy to read and operate.

Built-in efficient cool system

Advanced and high efficient cooling heatsink designed accompanied with over temperature protection. If the temperature become too high due to continuous use, it will change to safe mode automatically and never shutdown.

Built-in indicator

An integrated light indicator monitors the light intensity during operation.

4 direction Navigate key

Easy to operate by one finger
Within the key, 4 directions (up, down, left, right) are included. Easy to understand and easy to operate.

Germproof progress

Keep it clean always
Used by the germproof material in the plastic cover.

Support both cordless and plug-in types

Built-in high capacity lithium-ion battery
Using lithium-ion battery (2200mAh/7.4v) or and AC power source to operate is easy. Usually 800 times for 10 seconds

